



Technical Data Sheet

GLAZING VISION

Eaves Flushglaze

FG-E-TDS-v1.5-31.08.2018

Name: Eaves Flushglaze

Code: 402

Type: Fixed Rooflight

Description:

A fixed glazing system comprising powder coated aluminium extrusion and double glazed units. Designed for installation along building eaves. Can also be installed to span opposing gables or as a short extension to an additional building. Available in either single or multipart format, the latter (bespoke) consisting of multiple glazing sections. Flushglaze rooflights are designed to provide maximum daylight with minimal visible internal structure.

Features:

No visible exterior fixings. Lead (or other material) flashing used to hide structural fixings leaving a sleek external finish. Low profile vertical frames mated to high strength overhead support angles. Cill flashing detail to ensure water runs off.

Suite of product support data including; sales drawings, schedule and manufacturing information.

| | | | | |
|------------------|------------------|-------|------------------|--------|
| Kerb Dimensions: | Min Height: | 400mm | Max Height : | 4000mm |
| | Min Span: | 400mm | Max Span: | 4000mm |
| | Min Width: | 400mm | Max Width: | 1600mm |
| | Min Wall Offset: | 0mm | Max Wall Offset: | 100mm |
| | Min Pitch: | 3° | Max Pitch: | 50° |

Example Glass Specification: Outer: 6mm Clear Toughened
Spacer: 14mm Black Silicone Sealed Argon filled cavity with warm edge spacer
Inner: 9.5mm Clear Soft Low E Heat Strengthened Laminated

Thermal Performance (U-Value): Overall U-Value = 1.3 W/(m²K) (Based upon dimensions: 1600 Width x 2000 Span x 2000 Height with above example glass specification)



Technical Data Sheet

GLAZING VISION

Eaves Flushglaze

FG-E-TDS-v1.5-31.08.2018

| | |
|--------------------|--|
| Standard Colour: | RAL 7015 Slate grey |
| Rooflight Control: | N/A |
| Power Supply: | N/A |
| Drive Mechanism: | N/A |
| Seals: | Silicone. |
| Security: | Secured to kerb with structural fixings. |
| Use for Access: | N/A |

| CAD Drawings: | Drawing Number | Description |
|---------------|----------------|---------------------------------------|
| | 402-ASS-056 | Double glazed eaves detail (3 sheets) |

| | | | | |
|------------------|------------------|---------------|-----------------------------|--------------|
| Optional Extras: | Remote Control: | N/A | RITEC Coating: | Yes |
| | Solenoid Bolt: | N/A | Dual Colour: | No |
| | Wall Abutted: | Yes | Special Colour: | Yes |
| | Thermostat: | N/A | Round: | No |
| | BMS Integration: | N/A | Downlighter: | No |
| | Trickle Vents: | Yes (bespoke) | Multi-Part: | Bespoke only |
| | | | Multi-Part with Glass Fins: | Bespoke only |

Glazing Vision Ltd
Saw Mills Road, Diss, Norfolk IP22 4RG

For technical support please call
01379 658300

or visit us at
www.glazingvision.co.uk/resources

or email us at
technicalsales@glazingvision.co.uk